



MC-FAR Series Portable Articulating Jib Crane 250, 500 & 1,000 lbs.

Capacity (Pounds)	Model	Hub (ft.)	Span (ft.)	"A" (ft.)	"B" (ft.)	"C" (in.)	OAH	Base (in.)	Unit Weight
250	MC2588-FAR	8	8	5	3	16-1/2	9' 4-1/2"	4 x 48	2,776
250	MC25810-FAR	8	10	6	4	16-1/2	9' 4-1/2"	6 x 48	4,111
250	MC25812-FAR	8	12	7	5	16-1/2	9' 4-1/2"	7 x 48	4,800
250	MC25108-FAR	10	8	5	3	16-1/2	11' 4-1/2"	4 x 48	2,814
250	MC251010-FAR	10	10	6	4	16-1/2	11' 4-1/2"	6 x 48	4,149
250	MC251012-FAR	10	12	7	5	16-1/2	11' 4-1/2"	7 x 48	4,838
250	MC25128-FAR	12	8	5	3	16-1/2	13' 4-1/2"	4 x 48	2,852
250	MC251210-FAR	12	10	6	4	16-1/2	13' 4-1/2"	6 x 48	4,187
250	MC251212-FAR	12	12	7	5	16-1/2	13' 4-1/2"	7 x 48	4,876
500	MC588-FAR	8	8	5	3	19-1/2	9' 7-1/2"	7 X 48	4,808
500	MC5810-FAR	8	10	6	4	19-1/2	9' 7-1/2"	6 X 60	6,175
500	MC5812-FAR	8	12	7	5	19-1/2	9' 7-1/2"	6 X 60	6,315
500	MC5108-FAR	10	8	5	3	19-1/2	11' 7-1/2"	7 X 48	4,846
500	MC51010-FAR	10	10	6	4	19-1/2	11' 7-1/2"	6 X 60	6,213
500	MC51012-FAR	10	12	7	5	19-1/2	11' 7-1/2"	6 X 60	6,359
500	MC5128-FAR	12	8	5	3	19-1/2	13' 7-1/2"	7 X 48	4,884
500	MC51210-FAR	12	10	6	4	19-1/2	13' 7-1/2"	6 X 60	6,251
500	MC51212-FAR	12	12	7	5	19-1/2	13' 7-1/2"	6 X 60	6,404
1,000	MC188-FAR	8	8	5	3	20-1/2	9' 8-1/2"	6 X 60	6,284
1,000	MC1810-FAR	8	10	6	4	20-1/2	9' 8-1/2"	7 X 60	7,487
1,000	MC1812-FAR	8	12	7	5	20-1/2	9' 8-1/2"	8 X 60	8,558
1,000	MC1108-FAR	10	8	5	3	20-1/2	11' 8-1/2"	6 X 60	6,328
1,000	MC11010-FAR	10	10	6	4	20-1/2	11' 8-1/2"	7 X 60	7,543
1,000	MC11012-FAR	10	12	7	5	20-1/2	11' 8-1/2"	8 X 60	8,614
1,000	MC1128-FAR	12	8	5	3	20-1/2	13' 8-1/2"	6 X 60	6,373
1,000	MC11210-FAR	12	10	6	4	20-1/2	13' 8-1/2"	7 X 60	7,599
1,000	MC11212-FAR	12	12	7	5	20-1/2	13' 8-1/2"	8 X 60	8,670

Effective 8/2019 Does not require concrete foundation. Can be moved with fork truck. Solid steel base with 4" x 8" fork pockets on 22" fork centers.

Accessories:

- FAR-TEC1 Single Top Entry Electrical Collector (includes 12/4 SO cord in auxiliary boom)
- FAR-TEC2 Double Top Entry Electrical Collectors (includes 12/4 SO cord in auxiliary boom)
- FAR-TAS1 Single Air Swivel (includes 1/2 air hose in auxiliary boom)
- FAR-TAS2 Double Air Swivel (includes 1/2 air hose in auxiliary boom)
- RS Weld-on Rotation Stops (pair) - field mount
- FLRS-C Adjustable Collar Rotation Stop—(2) collars rotated to desired location
- FAR-RL Indexing Rotation Lock for auxiliary boom