



FL-WS Series Foundationless Floor Mounted Work Station Jib Crane 1/4 Ton Capacity

Capacity (Pounds)	Model	Hub	Span	Beam Height	Base Diameter	Unit Weight
500	FL586-WS	8'	6'	6"	28"	433#
500	FL588-WS	8'	8'	6"	28"	477#
500	FL5810-WS	8'	10'	6"	28"	511#
500	FL5812-WS	8'	12'	6"	28"	665#
500	FL5106-WS	10'	6'	6"	28"	468#
500	FL5108-WS	10'	8'	6"	28"	512#
500	FL51010-WS	10'	10'	6"	28"	541#
500	FL51012-WS	10'	12'	6"	28"	720#
500	FL5126-WS	12'	6'	6"	28"	518#
500	FL5128-WS	12'	8'	6"	28"	547#
500	FL51210-WS	12'	10'	6"	28"	581#
500	FL51212-WS	12'	12'	6"	28"	765#

Effective 2/17

Price includes enclosed track and trolley.

NOTE:

Existing concrete must be a minimum of 6" thick reinforced with a minimum 3,000 psi (5 bag mix), soil pressure must support 2,500 psi.

Concrete in and around the area (6' x 6') of the base plate must be free of cracks and must appear in good condition.

All units have 26" BD and 22" BC 6 holes 1-1/4" diameter.

All foundations should be checked by a structural engineer.

OPTIONS: Tagline Kits
Hoists

