



Stainless Steel

FL-Series Foundationless Floor Mounted Jib Crane 1/4 Ton Capacity

Capacity (Pounds)	Model	Hub	Span	Beam Height	Flange Width	Base Diameter	Unit Weight
500	FL586-SS	8'	6'	6"	4"	28"	490#
500	FL588-SS	8'	8'	6"	4"	28"	522#
500	FL5810-SS	8'	10'	6"	4"	28"	554#
500	FL5812-SS	8'	12'	6"	4"	28"	681#
500	FL5814-SS	8'	14'	8"	5-1/4"	28"	912#
500	FL5106-SS	10'	6'	6"	4"	28"	528#
500	FL5108-SS	10'	8'	6"	4"	28"	560#
500	FL51010-SS	10'	10'	6"	4"	28"	592#
500	FL51012-SS	10'	12'	6"	4"	28"	725#
500	FL51014-SS	10'	14'	8"	5-1/4"	28"	968#
500	FL5126-SS	12'	6'	6"	4"	28"	566#
500	FL5128-SS	12'	8'	6"	4"	28"	598#
500	FL51210-SS	12'	10'	6"	4"	28"	630#
500	FL51212-SS	12'	12'	6"	4"	28"	770#
500	FL51214-SS	12'	14'	8"	5-1/4"	28"	1,036#

Effective 11/2019

NOTE:

- Existing concrete must be a minimum of 6" thick reinforced with a minimum 3,000 psi (5 bag mix), soil pressure must support 2,500 psi.
- Concrete in and around the area (6' x 6') of the base plate must be free of cracks and must appear in good condition.
- All units have 28" diameter base and 24" bolt circle 8 holes 1-1/4" diameter.
- All foundations should be checked by a structural engineer.

Options: TG-SS Stainless Tagline Kit with S'Hooks

AB-FL5-SS Stainless Epoxy Anchor Kits, 8 bolts

28D8 Bolt Pattern Templates

Hoists & Trolleys - Contact Sales

