



FL-WS Series Foundationless Floor Mounted Work Station Jib Crane 1/8 Ton Capacity

Capacity (Pounds)	Model	Hub	Span	Beam Height	Base Diameter	Unit Weight	
250	FL2586-WS	8'	6'	6"	26"	418#	
250	FL2588-WS	8'	8'	6"	26"	462#	
250	FL25810-WS	8'	10'	6"	26"	496#	
250	FL25812-WS	8'	12'	6"	26"	650#	
250	FL25106-WS	10'	6'	6"	26"	453#	
250	FL25108-WS	10'	8'	6"	26"	497#	
250	FL251010-WS	10'	10'	6"	26"	525#	
250	FL251012-WS	10'	12'	6"	26"	705#	
250	FL25126-WS	12'	6'	6"	26"	503#	
250	FL25128-WS	12'	8'	6"	26"	532#	
250	FL251210-WS	12'	10'	6"	26"	566#	
250	FL251212-WS	12'	12'	6"	26"	750#	

Effective 2/17

Price includes enclosed track and trolley.

NOTE:

Existing concrete must be a minimum of 6" thick reinforced with a minimum 3,000 psi (5 bag mix), soil pressure must support 2,500 psi.

Concrete in and around the area (6' x 6') of the base plate must be free of cracks and must appear in good condition.

All units have 26" BD and 22" BC 6 holes 1-1/4" diameter. All foundations should be checked by a structural engineer.

OPTIONS: Tagline Kits
Hoists

