

Lifting Beams

Model 20 - Low Headroom Multiple Spread Lifting Beam

Ideal where headroom is limited.



**QUICKSHIP
PROGRAM**

PRODUCT FEATURES:

- Beams over 6' and longer have 3 spreads.
- 3' & 4' beams have 2 spreads.
- Swivel hooks with hook latches standard.
- Wide range of sizes and capacities available.
- Complies with ASME standards.

STANDARD FEATURE:

Three spreads to adjust to the load

- Outside spread
- Middle spread (outside less 1')
- Inside spread (outside less 2')


SPECIFICATIONS

Capacity (tons)	Model Number HR Headroom (in.) Weight (lbs.)	Outside Spread (feet)						
		3	4	6	8	10	12	
1/2	Model Number	20-1/2-3	20-1/2-4	20-1/2-6	20-1/2-8	20-1/2-10	20-1/2-12	
	HR Headroom	12-3/4	12-3/4	12-3/4	12-3/4	13-3/4	13-3/4	
	Weight	40	50	65	95	140	160	
1	Model Number	20-1-3	20-1-4	20-1-6	20-1-8	20-1-10	20-1-12	
	HR Headroom	12-3/4	12-3/4	13-3/4	13-3/4	14-3/4	15-3/4	
	Weight	40	50	85	115	165	230	
2	Model Number	20-2-3	20-2-4	20-2-6	20-2-8	20-2-10	20-2-12	
	HR Headroom	13-3/4	13-3/4	14-3/4	16-1/2	17-1/2	18-1/4	
	Weight	50	65	100	165	230	315	
3	Model Number	20-3-3	20-3-4	20-3-6	20-3-8	20-3-10	20-3-12	
	HR Headroom	15-1/4	15-1/4	16-1/4	17-1/4	18-1/4	22-1/2	
	Weight	70	80	140	200	275	415	
5	Model Number	20-5-3	20-5-4	20-5-6	20-5-8	20-5-10	20-5-12	
	HR Headroom	19-1/2	20-1/2	21-1/2	25-1/2	25-1/2	27-1/2	
	Weight	115	145	205	325	390	580	
7-1/2	Model Number	20-7 1/2-3	20-7 1/2-4	20-7 1/2-6	20-7 1/2-8	20-7 1/2-10	20-7 1/2-12	
	HR Headroom	22-1/2	23-1/2	25-1/4	27-1/4	27-1/4	30-1/4	
	Weight	135	170	265	415	500	910	
10	Model Number	20-10-3	20-10-4	20-10-6	20-10-8	20-10-10	20-10-12	
	HR Headroom	23-1/4	25-1/4	27-1/4	27-1/4	30-1/4	30-1/4	
	Weight	150	205	335	420	775	910	
15	Model Number	20-15-3	20-15-4	20-15-6	20-15-8	20-15-10	20-15-12	
	HR Headroom	28-1/2	30-1/2	30-1/2	33-1/2	33-1/2	40-1/4	
	Weight	215	295	375	685	820	1180	
20	Model Number	20-20-3	20-20-4	20-20-6	20-20-8	20-20-10	20-20-12	
	HR Headroom	38-3/4	38-3/4	38-3/4	38-3/4	41-1/2	41-1/2	
	Weight	370	435	575	710	1070	1235	
25	Model Number		20-25-4	20-25-6	20-25-8	20-25-10	20-25-12	
	HR Headroom		41-3/8	41-3/8	44-3/8	44-3/8	44-3/8	
	Weight		470	590	925	1100	1650	
30	Model Number		20-30-4	20-30-6	20-30-8			
	HR Headroom		45-1/2	45-1/2	48-1/4			
	Weight		525	660	1010			
40	Model Number		20-40-4	20-40-6				
	HR Headroom		44-3/4	47-3/4				
	Weight		600	930				

Other sizes available, consult factory.


Lifting Beams

Recommend faspins (Option B) if frequent hook position changes (spread) are required.



SPECIFICATIONS


Outside Spread (feet)							Other Dimensions (in.)	
14	16	18	20	24	30			
20-1/2-14 14-3/4 230	20-1/2-16 15-3/4 305	20-1/2-18 16-3/4 400	20-1/2-20 16-3/4 450	20-1/2-24 20-1/4 830	20-1/2-30 22-1/4 1340		A=7/8 B=3 C=5	T=3/4 O=7/8
20-1-14 16-3/4 320	20-1-16 18-1/2 415	20-1-18 20-1/4 605	20-1-20 20-1/4 675	20-1-24 22-1/4 1095			A=7/8 B=3 C=5	T=3/4 O=7/8
20-2-14 20-1/4 480	20-2-16 20-1/4 540	20-2-18 24-3/4 800	20-2-20 24-3/4 900	20-2-24 27-3/4 1730			A=7/8 B=3 C=5	T=3/4 O=7/8
20-3-14 24-1/2 650	20-3-16 24-1/2 730	20-3-18 27-1/2 1295	20-3-20 27-1/2 1450	20-3-24 27-1/2 1765			A=1-1/4 B=3 C=5	T=1 O=1
20-5-14 27-1/2 690	20-5-16 30-1/4 1210	20-5-18 30-1/4 1340	20-5-20 30-1/4 1505	20-5-24 33-1/4 2275			A=2 B=4 C=7	T=1-1/4 O=1-15/16
20-7 1/2-14 30-1/4 1070	20-7 1/2-16 30-1/4 1600	20-7 1/2-18 33 1665					A=2 B=4 C=7	T=1-1/4 O=1-1/2
20-10-14 30-1/4 1075	20-10-16 33 1500	20-10-18 33 1670					A=2 B=4 C=7	T=1-1/4 O=1-9/16
20-15-14 40-1/4 1385							A=2-1/2 B=5 C=9	T=1-1/2 O=2-1/16
See pages A.10 and A.11 for these capacities and sizes.							A=2-1/2 B=5 C=9	T=1-1/2 O=2-1/4
							A=3 B=6 C=12	T=1-3/4 O=2-1/4
							A=3-1/2 B=7 C=16	T=2 O=2-1/4
							A=3-1/2 B=7 C=16	T=2-1/2 O=3



OPTION A

Extra Holes or Different Placement of Holes


Allows multiple hook positioning beyond standard spreads. Specify number and spread(s) required.



OPTION B

Faspins


For ease of positioning hooks with quick release. Specify number required.



OPTION C

Extra Hooks

Allows for multiple pick points. Specify number required.



OPTION D

Pin Type Bail

Lifting pin located between structural channel. (Hoist hook information must be supplied.)



OPTION E

Shackle Lug

Lifting lug with shackle. (Headroom may change.)