



FL-WS Series Foundationless Floor Mounted Work Station Jib Crane 1/2 Ton Capacity

Capacity (Pounds)	Model	Hub	Span	Beam Height	Base Diameter	Unit Weight
1000	FL186-WS	8'	6'	6"	30"	533#
1000	FL188-WS	8'	8'	6"	30"	602#
1000	FL1810-WS	8'	10'	8"	30"	806#
1000	FL1812-WS	8'	12'	8"	30"	931#
1000	FL1106-WS	10'	6'	6"	30"	613#
1000	FL1108-WS	10'	8'	6"	30"	652#
1000	FL11010-WS	10'	10'	8"	30"	896#
1000	FL11012-WS	10'	12'	8"	30"	976#
1000	FL1126-WS	12'	6'	6"	30"	623#
1000	FL1128-WS	12'	8'	6"	30"	677#
1000	FL11210-WS	12'	10'	8"	30"	916#
1000	FL11212-WS	12'	12'	8"	30"	1006#

Effective 2/17

Price includes enclosed track and trolley.

NOTE:

Existing concrete must be a minimum of 6" thick reinforced with a minimum 3,000 psi (5 bag mix), soil pressure must support 2,500 psi.

Concrete in and around the area (6' x 6') of the base plate must be free of cracks and must appear in good condition.

All units have 26" BD and 22" BC 6 holes 1-1/4" diameter.

All foundations should be checked by a structural engineer.

OPTIONS: Tagline Kits
Hoists

